

S6P34 GREEN

Cartridge operated foam fire extinguisher



PASTOR

Feuerlöscher

SCHAUM G L 34A 144B

-  **SICHERUNGSLASCHE
HERAUSZIEHEN**
REMOVE SAFETY DEVICE
-  **ROTE HAUBE
KRÄFTIG SCHLAGEN**
STRIKE ACTIVATION CAP
-  **LÖSCHPISTOLE
BETÄTIGEN**
SQUEEZE NOZZLE PISTOL



Vorsicht bei spannungsführenden Anlagen.
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Nach jeder Bedienung muss behälterförmig spätestens alle 2 Jahre auf Funktionsfähigkeit überprüft
bei neuen Lösch-/Trennmittel und Ersatzteile verwendet, die mit der Zulassung übereinstimmen.

TEMPERATURBEREICH: -5°C / +40°C ZULASSUNGSNUMMER: SP 105/11108 030

LÖSCHMITTEL: 4,5 l WASSER + 1,2 l Pastormix TYP: S6P34 Green

GEWICHT: 75 g CO₂

PASTOR DEUTSCHLAND 43721 Nean (NRW) Industriestrasse 43 Deutschland MADE IN THE EU PASTOR DEUTSCHLAND DE

PASTOR DEUTSCHLAND

S6P34 GREEN

Cartridge operated foam fire extinguisher



TECHNICAL DATA

Type	S6P34 GREEN
Design	Cartridge operated foam fire extinguisher
Extinguishing agent quantity	6 l
Extinguishing agent	Foam / Fluorine-free
Propellant	CO ₂
Extinguishing performance	34A / 144B
Extinguishing agents units	34A (10) / 144B (9)
Functional range	+5°C - +60°C
Operating time	45-50 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable hose incl. extinguishing nozzle with optimised foaming
Weight	Approx. 10.75 kg
Height	Approx. 559 mm
Diameter	Approx. 150 mm

- Cartridge operated fire extinguisher, for more sustainability
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Extinguishing agent contains no PFAS additives
- Maintenance-friendly premium appliance
- Glass fibre reinforced plastic fitting with push-button release
- M74-Threaded opening for best maintenance
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Internal corrosion-resistant propellant bottle
- Wall bracket and foot ring
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU

PASTOR-DEUTSCHLAND.DE