

SK6P34 GREEN

Cartridge operated foam fire extinguisher



PASTOR

Feuerlöscher
SCHAUM 6 L 34A 144B

-  **SICHERUNGSLASCHE
HERAUSZIEHEN**
REMOVE SAFETY DEVICE
-  **ROTE HAUBE
KRÄFTIG SCHLAGEN**
STRIKE ACTIVATION CAP
-  **LÖSCHPISTOLE
BETÄTIGEN**
SQUEEZE NOZZLE PISTOL



Vorsicht bei spannungsführenden Anlagen.
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Nur zum Bekämpfen von brennenden Flüssigkeiten und Feststoffen geeignet.
Nicht für Kohlen-, Öl- und Fettbrände verwenden, die mit der Löschempfindlichkeit

TEMPERATURBEREICH: -10°C/+60°C LADUNGSGEWICHT: 800/1100g

AGENTSCHAFT: 4.011 WAGNER - 0111 Pastor/MS TYP: SK6P34 GREEN

NEUHEITEN: 75 g CO₂

PASTOR DEUTSCHLAND 42701 Hesse (HBM) MADE IN THE EU
Bühnenstraße 43 Deutschland PASTOR-DEUTSCHLAND 34

PASTOR DEUTSCHLAND

SK6P34 GREEN

Cartridge operated foam fire extinguisher



TECHNICAL DATA

Type	SK6P34 GREEN
Design	Cartridge operated foam fire extinguisher
Extinguishing agent quantity	6 l
Extinguishing agent	Foam / Fluorine-free
Propellant	CO ₂
Extinguishing performance	34A / 144B
Extinguishing agents units	34A (10) / 144B (9)
Functional range	+5°C - +60°C
Operating time	45-50 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable hose incl. extinguishing nozzle with optimised foaming
Weight	Approx. 10.85 kg
Height	Approx. 559 mm
Diameter	Approx. 150 mm

- Cartridge operated fire extinguisher, for more sustainability
- Fluorine-free foam / Extinguishing agent contains no PFAS additives
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Maintenance-friendly premium appliance
- Glass fibre reinforced plastic fitting with push-button release
- M74-Threaded opening for best maintenance
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Internal corrosion-resistant propellant bottle
- Wall bracket and foot ring
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU

PASTOR-DEUTSCHLAND.DE