

K2 Steel

Carbon dioxide fire extinguisher



PASTOR DEUTSCHLAND

The photo shown is for reference only, the actual product may differ.

K2 Steel

Carbon dioxide fire extinguisher



TECHNICAL DATA

Type	K2 Steel
Design	Carbon dioxide fire extinguisher
Extinguishing agent quantity	2 kg
Extinguishing agent	Carbon dioxide
Propellant	CO ₂
Extinguishing performance	34B
Extinguishing agents units	34B (2)
Functional range	-30°C - +60°C
Operating time	8-10 s
Throwing distance	3-4 m
Hose / nozzle	Snow tube
Weight	Approx. 6 kg
Height	Approx. 570 mm
Diameter	Approx. 103 mm

- Carbon dioxide fire extinguisher, for clean fire fighting
- Durable brass push lever fitting
- Reinforced carrying handle with balanced carrying properties
- Intuitive handling with simple release mechanism
- The appliance is immediately ready for use when the locking pin is pulled out
- Metal clamping strap / Wall bracket
- UV-resistant, durable plastic components
- UV weather-resistant flat snow tube
- Steel container with UV-resistant, durable polyester resin powder coating
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Frost-resistant down to -30°C

LMD: 01-04-24, 20:29

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU

PASTOR-DEUTSCHLAND.DE