K5 Alu

Carbon dioxide fire extinguisher







PASTOR DEUTSCHLAND

K5 Alu

Carbon dioxide fire extinguisher



TECHNICAL DATA

K5 Alu Type Design Carbon dioxide fire extinguisher **Extinguishing agent quantity** 5 kg **Extinguishing agent** Carbon dioxide **Propellant** CO, **Extinguishing performance** 89B 89B (5) **Extinguishing agents units** -30°C - +60°C **Functional range** 14-16 s **Operating time** 3-4 m **Throwing distance**

- Carbon dioxide fire extinguisher, for clean fire fighting
- Durable brass push lever fitting
- Reinforced carrying handle with balanced carrying properties
- Intuitive handling with simple release mechanism
- The appliance is immediately ready for use when the locking pin is pulled out
- Metal clamping strap / Wall bracket
- UV-resistant, durable plastic components
- UV weather-resistant hose with special flat snow tube
- Aluminium container with UV-resistant, durable polyester resin powder coating
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Frost-resistant down to -30°C

LMD: 01-04-24, 20:29

Hose / nozzle

Weight

Height

Diameter





Quality high-pressure hose

Approx. 790 mm when mounting the

snow pipe on the metal clamping strap

with snow tube

Approx. 12 kg

Approx. 890 mm

Approx. 152 mm

42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU

PASTOR-DEUTSCHLAND.DE