K5 Steel

B

Carbon dioxide fire extinguisher



The photo shown is for reference only, the actual product may diffe

K5 Steel Carbon dioxide fire extinguisher



TECHNICAL DATA

Туре	K5 Steel
Design	Carbon dioxide fire extinguisher
Extinguishing agent quantity	5 kg
Extinguishing agent	Carbon dioxide
Propellant	C0 ₂
Extinguishing performance	89B
Extinguishing agents units	89B (5)
Functional range	-30°C - +60°C
Operating time	14-16 s
Throwing distance	3-4 m
Hose / nozzle	Quality high-pressure hose with snow tube
Weight	Approx. 14.7 kg
Height	Approx. 890 mm Approx. 790 mm when mounting the snow pipe on the metal clamping strap
Diameter	Approx. 138 mm

Carbon dioxide fire extinguisher, for clean fire fighting **Durable brass push lever fitting Reinforced carrying handle** with balanced carrying properties Intuitive handling with simple release mechanism The appliance is immediately ready for use when the locking pin is pulled out Metal clamping strap / Wall bracket UV-resistant, durable plastic components **UV** weather-resistant hose with special flat snow tube Steel container with UV-resistant, durable polyester resin powder coating Suitable for electrical systems up to 1000 volts, minimum distance 1 m Frost-resistant down to -30°C

LMD: 01-04-24, 20:29



42781 Haan (NRW) Bahnhofstraße 48 Deutschland

MADE IN THE EU PASTOR-DEUTSCHLAND.DE

Printing errors, mistakes, technical or other changes as well as changes in the availability of individual products are expressly reserved. PASTOR Deutschland GmbH, 2024