

PD2Z13

Stored pressure ABC dry powder fire extinguisher



PASTOR

Feuerlöscher

PULVER ABC 2 KG 13A 70B C

-  **SICHERUNGSTIFT
ENTFERNEN**
PULL OUT SAFETY PIN
-  **DÜSE AUF DEN
BRANDHERD RICHTEN**
AIM NOZZLE AT BASE OF FIRE
-  **HEBEL
BETÄTIGEN**
SQUEEZE VALVE



Vorsicht bei spannungsführenden Anlagen.
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Nach jeder Benutzung des handgeführten Löscher spätestens alle 2 Jahre auf Druckverlust überprüfen.
Bei mangelhafter Sicherheit und Integrität neuverpacken, für eine weitere Verwendung.

TEMPERATURBEREICH: -30°C/+50°C TROCKENMITTEL: STICKSTOFF 14 bar/20°C

LEISTUNGSFÄHIGKEIT: ABC PULVER (GP 95/102) ZULASSUNGSRUMMER: SP 471/11 EN 151

NETTOGEWICHT: 2,0 kg TYP: PULVER

PASTOR DEUTSCHLAND  43781 Bonn (BRN) **MADE IN THE EU**
Bakkerstraße 43
Deutschland PASTOR-DEUTSCHLAND.DE



PASTOR

DEUTSCHLAND

PD2Z13

Stored pressure ABC dry powder fire extinguisher



TECHNICAL DATA

| | |
|------------------------------|---|
| Type | PD2Z13 |
| Design | Stored pressure ABC dry powder fire extinguisher |
| Extinguishing agent quantity | 2 kg |
| Extinguishing agent | ABC dry powder |
| Propellant | N ₂ |
| Extinguishing performance | 13A / 70B / C |
| Extinguishing agents units | 13A (4) / 70B (4) |
| Functional range | -30°C - +60°C |
| Operating time | 11-12 s |
| Throwing distance | 4-5 m |
| Hose / nozzle | Extinguishing nozzle |
| Weight | Approx. 3.79 kg |
| Height | Approx. 335 mm |
| Diameter | Approx. 110 mm |

- Stored pressure fire extinguisher, the budget device
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Durable M30 brass fitting with test and filling valve
- Intuitive handling with simple release mechanism
- When the locking pin is pulled the device is immediately ready for use
- Reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- Special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating
- Wall bracket
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Frost-resistant down to -30°C

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU
PASTOR-DEUTSCHLAND.DE