# **PD6Z34**

## Stored pressure ABC dry powder fire extinguisher











PASTOR DEUTSCHLAND

## **PD6Z34**

### Stored pressure ABC dry powder fire extinguisher







#### TECHNICAL DATA

Type PD6Z34

Design Stored pressure

ABC dry powder fire extinguisher

Extinguishing agent quantity 6 kg

**Extinguishing agent** ABC dry powder

Propellant N<sub>2</sub>

Extinguishing performance 34A / 233B / C

Extinguishing agents units 34A (10) / 233 (15)

Functional range -30°C - +60°C

Operating time 18-20 s

Throwing distance 4-6 m

Hose / nozzle Flexible, durable quality hose incl. extinguishing nozzle

Weight Approx. 9.56 kg

Height Approx. 510 mm

**Diameter** Approx. 150 mm

 Stored pressure fire extinguisher, the budget device

- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Durable M30 brass fitting with test and filling valve
- Intuitive handling with simple release mechanism
- When the locking pin is pulled the device is immediately ready for use
- Reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV weather-resistant hose with special nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating
- Wall bracket
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Frost-resistant down to -30°C

LMD: 29-03-24, 18:48





42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU

**PASTOR-DEUTSCHLAND.DE**