

# PD6Z43

## Stored pressure ABC dry powder fire extinguisher



# PASTOR

### Feuerlöscher

PULVER ABC 6 KG 43A 233B C

-  **SICHERUNGSSTIFF  
ENTFERNEN**  
PULL OUT SAFETY PIN
-  **SCHLAUCH AUF DEN  
BRANDHERD RICHTEN**  
AIM NOZZLE AT BASE OF FIRE
-  **HEBEL  
BETÄTIGEN**  
SQUEEZE VALVE



Vorsicht bei spannungsführenden Anlagen.  
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Nach jeder Nutzung von befüllten Löschern spätestens alle 2 Jahre auf Funktionsfähigkeit überprüfen.  
Vor jedem Lösch-/Trennstrahl und Sprühdüse verwenden, die mit der Zeichnung übereinstimmen.

FUNKTIONSBEREICH: -20°C / +60°C FREIWEITEN: 51 CM bis 114 cm / 170°C

LÖSCHMITTEL: ABC PULVER (SP 95/12) ZULASSUNGSNUMMER: SP 232/10 008 001

PL: 20 bar TYP: PD6Z43

PASTOR DEUTSCHLAND 43201 Bonn (RWL) Röhrenstraße 44 Deutschland MADE IN THE EU PASTOR-DEUTSCHLAND.DE



# PASTOR DEUTSCHLAND

# PD6Z43

## Stored pressure ABC dry powder fire extinguisher



### TECHNICAL DATA

Type	PD6Z43
Design	Stored pressure ABC dry powder fire extinguisher
Extinguishing agent quantity	6 kg
Extinguishing agent	ABC dry powder
Propellant	N <sub>2</sub>
Extinguishing performance	43A / 233B / C
Extinguishing agents units	43A (12) / 233B (15)
Functional range	-30°C - +60°C
Operating time	18-20 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable quality hose incl. extinguishing nozzle
Weight	Approx. 9.56 kg
Height	Approx. 510 mm
Diameter	Approx. 150 mm

- Stored pressure fire extinguisher, the budget device
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Durable M30 brass fitting with test and filling valve
- Intuitive handling with simple release mechanism
- When the locking pin is pulled the device is immediately ready for use
- Reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV weather-resistant hose with special nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating
- Wall bracket
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Frost-resistant down to -30°C

LMD: 29-03-24, 18:48

**PASTOR**  
DEUTSCHLAND



42781 Haan (NRW)  
Bahnhofstraße 48  
Deutschland

**MADE IN THE EU**  
**PASTOR-DEUTSCHLAND.DE**