

PD6Z55

Stored pressure ABC dry powder fire extinguisher



PASTOR DEUTSCHLAND

PD6Z55

Stored pressure ABC dry powder fire extinguisher



TECHNICAL DATA

| | |
|------------------------------|--|
| Type | PD6Z55 |
| Design | Stored pressure ABC dry powder fire extinguisher |
| Extinguishing agent quantity | 6 kg |
| Extinguishing agent | ABC dry powder |
| Propellant | N ₂ |
| Extinguishing performance | 55A / 233B / C |
| Extinguishing agents units | 55A (15) / 233B (15) |
| Functional range | -30°C - +60°C |
| Operating time | 18-20 s |
| Throwing distance | 4-6 m |
| Hose / nozzle | Flexible, durable quality hose incl. extinguishing nozzle |
| Weight | Approx. 9.56 kg |
| Height | Approx. 510 mm |
| Diameter | Approx. 150 mm |

- Stored pressure fire extinguisher, the budget device
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Durable M30 brass fitting with test and filling valve
- Intuitive handling with simple release mechanism
- When the locking pin is pulled the device is immediately ready for use
- Reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV weather-resistant hose with special nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating
- Wall bracket
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Frost-resistant down to -30°C

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU
PASTOR-DEUTSCHLAND.DE