PD9Z55

Stored pressure ABC dry powder fire extinguisher







PASTOR Deutschland

PD9Z55

Stored pressure ABC dry powder fire extinguisher



TECHNICAL DATA

| Туре | PD9Z55 |
|------------------------------|-----------------------------------------------------------|
| Design | Stored pressure ABC dry powder fire extinguisher |
| Extinguishing agent quantity | 9 kg |
| Extinguishing agent | ABC dry powder |
| Propellant | N ₂ |
| Extinguishing performance | 55A / 233B / C |
| Extinguishing agents units | 55A (15) / 233 (15) |
| Functional range | -30°C - +60°C |
| Operating time | 24-26 s |
| Throwing distance | 5-6 m |
| Hose / nozzle | Flexible, durable quality hose incl. extinguishing nozzle |
| Weight | Approx. 13.55 kg |
| Height | Approx. 580 mm |
| Diameter | Approx. 170 mm |
| | |

LMD: 29-03-24, 18:48

| 9 kg | | fire-fighting, REACH-compliant |
|----------------|---|---------------------------------------------------------------------------|
| powder | - | Durable M30 brass fitting with test and filling valve |
| N ₂ | - | Intuitive handling with simple release mechanism |
| 33B / C | - | When the locking pin is pulled the device is |
| 233 (15) | | immediately ready for use |
| - +60°C | - | Reinforced carrying handle with balanced carrying properties |
| 24-26 s | - | UV-resistant, durable plastic components |
| 5-6 m | - | UV weather-resistant hose with special nozzle for |
| ity hose | | optimum discharge of the extinguishing agent |
| g nozzle | - | Steel container with UV-resistant, |
| 13.55 kg | | durable polyester resin powder coating |
| 580 mm | - | Wall bracket |
| 170 mm | - | Suitable for electrical systems up to 1000 volts, minimum distance 1 m |
| | | |

Stored pressure fire extinguisher,

High performance extinguishing agent for efficient

the budget device

Frost-resistant down to -30°C



42781 Haan (NRW) Bahnhofstraße 48 Deutschland

MADE IN THE EU PASTOR-DEUTSCHLAND.DE

Printing errors, mistakes, technical or other changes as well as changes in the availability of individual products are expressly reserved. @ PASTOR Deutschland GmbH, 2024

I