

PG12P55

Cartridge operated ABC dry powder fire extinguisher



PASTOR

Feuerlöscher

ABC PULVER 12 KG 55A 233B C

-  **SICHERUNGSLASCHE
HERAUSZIEHEN**
REMOVE SAFETY DEVICE
-  **ROTE HAUBE
KRÄFTIG SCHLAGEN**
STRIKE ACTIVATION CAP
-  **LÖSCHPISTOLE
BETÄTIGEN**
SQUEEZE NOZZLE PISTOL



Vorsicht bei spannungsführenden Anlagen.
Nur bis 1.000 Volt, Mindestabstand 1 Meter.

Nach jeder Bedienung am behälter (Lichter) spätestens alle 2 Jahre auf Funktionstauglichkeit überprüfen.
Für weitere Einzel- / Einzelteile und Ersatzteile verwenden, die mit der Lösung übereinstimmen.

TEMPERATURBEREICH: 30°C - 45°C ZULASSUNGSGRANIZ: TP 12/120 EN 120

LÖSCHMITTEL: ABC PULVER (SP 45/12) TYP: PULVER

NETZMittel: 120 g CO₂

PASTOR DEUTSCHLAND  42281 Hesse (BRUNN) Bahnhofstraße 42 Deutschland PASTOR DEUTSCHLAND DE  1270

PASTOR DEUTSCHLAND

PG12P55

Cartridge operated ABC dry powder fire extinguisher



TECHNICAL DATA

Type	PG12P55
Design	Cartridge operated ABC dry powder fire extinguisher
Extinguishing agent quantity	12 kg
Extinguishing agent	ABC dry powder
Propellant	CO ₂
Extinguishing performance	55A / 233B / C
Extinguishing agents units	55A (15) / 233B (15)
Functional range	-30°C - +60°C
Operating time	30-32 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable quality hose incl. extinguishing nozzle
Weight	Approx. 18.5 kg
Height	Approx. 594 mm
Diameter	Approx. 185 mm

- Cartridge operated fire extinguisher, for more sustainability
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Maintenance-friendly premium appliance
- Glass fibre reinforced plastic fitting with push-button release
- M74-Threaded opening for best maintenance
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating
- Internal corrosion-resistant propellant bottle
- Wall bracket and foot ring
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Frost-resistant down to -30°C

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU
PASTOR-DEUTSCHLAND.DE