

PG9P55

Cartridge operated ABC dry powder fire extinguisher



PASTOR

DEUTSCHLAND

PG9P55

Cartridge operated ABC dry powder fire extinguisher



TECHNICAL DATA

Type	PG9P55
Design	Cartridge operated ABC dry powder fire extinguisher
Extinguishing agent quantity	9 kg
Extinguishing agent	ABC dry powder
Propellant	CO ₂
Extinguishing performance	55A / 233B / C
Extinguishing agents units	55A (15) / 233B (15)
Functional range	-30°C - +60°C
Operating time	25-26 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable quality hose incl. extinguishing nozzle
Weight	Approx. 14.3 kg
Height	Approx. 562 mm
Diameter	Approx. 170 mm

- Cartridge operated fire extinguisher, for more sustainability
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Maintenance-friendly premium appliance
- Glass fibre reinforced plastic fitting with push-button release
- M74-Threaded opening for best maintenance
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating
- Internal corrosion-resistant propellant bottle
- Wall bracket and foot ring
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Frost-resistant down to -30°C

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU
PASTOR-DEUTSCHLAND.DE