

# S9P43

## Cartridge operated foam fire extinguisher



# PASTOR

### Feuerlöscher

SCHAUM 9 L 43A 233B

-  **SICHERUNGSLASCHE  
HERAUSZIEHEN**  
REMOVE SAFETY DEVICE
-  **ROTE HAUBE  
KRÄFTIG SCHLAGEN**  
STRIKE ACTIVATION CAP
-  **LÖSCHPISTOLE  
BETÄTIGEN**  
SQUEEZE NOZZLE PISTOL



Vorsicht bei spannungsführenden Anlagen.  
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Nach jeder Nutzung muss behälter wieder geladene alle 2 Jahre auf funktionstüchtigkeit überprüfen.  
Für weitere Details/Technikblätter und Ersatzteile verwenden, die mit der Zeichnung übereinstimmen.

FUNKTIONSBEREICH: 0°C/-40°C ZULASSUNGSNUMMER:

LÖSCHMITTEL: 9,0L WABW 90 + 1,0L Paste/Mix TYP: 16P43

NETZGEWICHT: 70 g CO<sub>2</sub>

PASTOR DEUTSCHLAND 43281 Hagen (NRW) Röhrenstraße 48 Deutschland PASTOR DEUTSCHLAND DE



# PASTOR DEUTSCHLAND

# S9P43

## Cartridge operated foam fire extinguisher



### TECHNICAL DATA

|                              |  |
|------------------------------|--|
| Type                         | S9P43  |
| Design                       | Cartridge operated foam fire extinguisher                                |
| Extinguishing agent quantity | 9 l  |
| Extinguishing agent          | Foam   |
| Propellant                   | CO <sub>2</sub>  |
| Extinguishing performance    | 43A / 233B   |
| Extinguishing agents units   | 43A (12) / 233B (15)   |
| Functional range             | 0°C - +60°C  |
| Operating time               | 58-60 s  |
| Throwing distance            | 4-6 m  |
| Hose / nozzle                | Flexible, durable hose incl. extinguishing nozzle with optimised foaming |
| Weight                       | Approx. 15 kg  |
| Height                       | Approx. 614 mm   |
| Diameter                     | Approx. 170 mm   |

- Cartridge operated fire extinguisher, for more sustainability
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Maintenance-friendly premium appliance
- Glass fibre reinforced plastic fitting with push-button release
- M74-Threaded opening for best maintenance
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Internal corrosion-resistant propellant bottle
- Wall bracket and foot ring
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

**PASTOR**  
DEUTSCHLAND



42781 Haan (NRW)  
Bahnhofstraße 48  
Deutschland

**MADE IN THE EU**  
**PASTOR-DEUTSCHLAND.DE**