

SD6Z27

Stored pressure foam fire extinguisher



PASTOR

Feuerlöscher

SCHAUM 6 L 27A 233B

-  SICHERUNGSTIFT
ENTFERNEN
PULL OUT SAFETY PIN
-  SCHLAUCH AUF DEN
BRANDHERD RICHTEN
AIM NOZZLE AT BASE OF FIRE
-  HEBEL
BETÄTIGEN
SQUEEZE VALVE



Vorsicht bei spannungsführenden Anlagen.
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Bei jeder Beladung muss behaltene Löschzeit spätestens alle 2 Jahre mit Fachhändler überprüfen.
Bei allen Lösch-/Technik- und Feuerwerke verwenden, die mit der Beladung übereinstimmen.

TEMPERATURBEREICH: 0°C/-40°C TREIBMITTEL: Stickstoff 14 bar/20°C
SCHWIMMSTREIFEN: 1,2% UNTER-4,0% ÜBER-4,0% ÜBER ZULASSUNGSNUMMER: 07 5902/24 04 08

PG: 20 bar TYP: SCHAUM

PASTOR DEUTSCHLAND 43781 Heese (BRN) MADE IN THE EU
Ruhohrstraße 42 PASTOR DEUTSCHLAND DE
Deutschland

PASTOR DEUTSCHLAND

SD6Z27

Stored pressure foam fire extinguisher



TECHNICAL DATA

Type	SD6Z27
Design	Stored pressure foam fire extinguisher
Extinguishing agent quantity	6 l
Extinguishing agent	Foam
Propellant	N ₂
Extinguishing performance	27A / 233B
Extinguishing agents units	27A (9) / 233B (15)
Functional range	0°C - +60°C
Operating time	38-40 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable hose incl. extinguishing nozzle with optimised foaming
Weight	Approx. 11 kg
Height	Approx. 590 mm
Diameter	Approx. 150 mm

- Stored pressure fire extinguisher, the budget device
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Extinguishing agent contains no PFAS additives
- Durable M30 brass fitting with test and filling valve
- Intuitive handling with simple release mechanism
- When the locking pin is pulled the device is immediately ready for use
- Reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV weather-resistant hose with special nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Wall bracket
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU
PASTOR-DEUTSCHLAND.DE