

SD9Z34

Stored pressure foam fire extinguisher



PASTOR

Feuerlöscher

SCHAUM 9 L 34A 233B

-  **SICHERUNGSTIFT
ENTFERNEN**
PULL OUT SAFETY PIN
-  **SCHLAUCH AUF DEN
BRANDHERD RICHTEN**
AIM NOZZLE AT BASE OF FIRE
-  **HEBEL
BETÄTIGEN**
SQUEEZE VALVE



Vorsicht bei spannungsführenden Anlagen.
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Bei jeder Bedienung vom Hersteller überprüfens alle 2 Jahre auf Funktionstauglichkeit überprüfen.
Bei nicht funktionierender oder Beschädigung sofort den Hersteller kontaktieren, der mit der Zulassung, Überwachung.

FUNKTIONSBEREICH: 0°C/32° - 40°C VERWENDUNG: STRECKSTOFF 16 bar/230°C

LEISTUNGSFÄHIGKEIT: EN15000-9.9L-4.5A/3.0B ZULASSUNGSNUMMER: SP 203/14.08.100

PS 17 bar ETP: 100014

PASTOR DEUTSCHLAND  42701 Rauen (BRN) **MADE IN THE EU**
Eisenhüttenstraße 48
Deutschland PASTOR-DEUTSCHLAND.DE  

PASTOR DEUTSCHLAND

SD9Z34

Stored pressure foam fire extinguisher



TECHNICAL DATA

Type	SD9Z34
Design	Stored pressure foam fire extinguisher
Extinguishing agent quantity	9 l
Extinguishing agent	Foam
Propellant	N ₂
Extinguishing performance	34A / 233B
Extinguishing agents units	34A (10) / 233B (15)
Functional range	0°C - +60°C
Operating time	54-56 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable hose incl. extinguishing nozzle with optimised foaming
Weight	Approx. 14.5 kg
Height	Approx. 640 mm
Diameter	Approx. 170 mm

- Stored pressure fire extinguisher, the budget device
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Extinguishing agent contains no PFAS additives
- Durable M30 brass fitting with test and filling valve
- Intuitive handling with simple release mechanism
- When the locking pin is pulled the device is immediately ready for use
- Reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV weather-resistant hose with special nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Wall bracket
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU
PASTOR-DEUTSCHLAND.DE