

# SD9Z43 GREEN

## Stored pressure foam fire extinguisher



# PASTOR

### Feuerlöscher

SCHAUM 9 L 43A 183B

- SICHERUNGSTIFT  
ENTFERNEN**  
PULL OUT SAFETY PIN
- SCHLAUCH AUF DEN  
BRANDHERD RICHTEN**  
AIM NOZZLE AT BASE OF FIRE
- HEBEL  
BETÄTIGEN**  
SQUEEZE VALVE



Vorsicht bei spannungsführenden Anlagen.  
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Nach jeder Bedienung des behälter Lösser spätestens alle 2 Jahre auf Funktionstauglichkeit überprüfen.  
Bei einem Leck / Unbehalt und Beschädigung verwenden, die mit der Adresse kommunizieren.

TEMPERATURBEREICH: +5°C/-40°C TREIBMITTEL: STICKSTOFF N<sub>2</sub>/CO<sub>2</sub>

LÖSCHMITTEL: PASTOR FF MIX ZULASSUNGNUMMER:

PF: 90 bar TYP: SD9Z43 GRN

**PASTOR** DEUTSCHLAND 42791 Heese (BRN) **MADE IN THE EU**  
Schleichstraße 44 PASTOR DEUTSCHLAND DE  
Deutschland

# PASTOR

## DEUTSCHLAND

# SD9Z43 GREEN

## Stored pressure foam fire extinguisher



### TECHNICAL DATA

Type	SD9Z43 GREEN
Design	Stored pressure foam fire extinguisher
Extinguishing agent quantity	9 l
Extinguishing agent	Foam / Fluorine-free
Propellant	N <sub>2</sub>
Extinguishing performance	43A / 183B
Extinguishing agents units	43A (12) / 183B (12)
Functional range	+5°C - +60°C
Operating time	54-56 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable hose incl. extinguishing nozzle with optimised foaming
Weight	Approx. 14.5 kg
Height	Approx. 640 mm
Diameter	Approx. 170 mm

- Stored pressure fire extinguisher, the budget device
- Fluorine-free foam / Extinguishing agent contains no PFAS additives
- High performance extinguishing agent for efficient fire-fighting
- REACH-compliant
- Glass fibre reinforced plastic fitting with push-button release
- Durable M30 brass fitting with test and filling valve
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable extinguishing gun, with special nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Wall bracket
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

**PASTOR**  
DEUTSCHLAND



42781 Haan (NRW)  
Bahnhofstraße 48  
Deutschland

**MADE IN THE EU**  
**PASTOR-DEUTSCHLAND.DE**