

# SF50-N2 GREEN -25

Mobile cartridge operated  
foam extinguishing trolley



**PASTOR**  
**DEUTSCHLAND**

# SF50-N2 GREEN -25

## Mobile cartridge operated foam extinguishing trolley



### TECHNICAL DATA

Type	S50-N2 -25 GREEN
Design	Mobile cartridge operated foam extinguishing trolley
Extinguishing agent quantity	50 l
Extinguishing agent	AB Foam / Fluorine-free
Propellant	N <sub>2</sub>
Extinguishing performance	A IV B
Extinguishing agents units	-
Functional range	-25°C - +60°C
Operating time	48 s
Throwing distance	4-6 m
Hose / nozzle	Flexible EPDM hose with pistol nozzle
Weight	Approx. 81 kg
Height	Approx. 1060 mm
Diameter	Approx. 470 mm

- **AB Extinguishing foam, particularly suitable for fire class B foam extinguishing agent**
- **Contains no PFAS additives / Fluorine-free foam**
- **Mobile extinguisher, in accordance with DIN EN 1866**
- **Sturdy chassis, stable stand, tilt-proof**
- **High-quality stainless steel container, corrosion-resistant, weather-resistant and durable coating**
- **Additional safety thanks to a built-in safety valve**
- **UV and weather-resistant, durable components**
- **Easy handling, designed for use by a single person**
- **Simple dosing of extinguishing agent**
- **High throw ranges for effective and safe firefighting**
- **Flexible EPDM hose with pistol nozzle for targeted firefighting, 5m**
- **Easy to maintain with large container opening**
- **Suitable for electrical systems up to 1000V, minimum distance 1m**
- **Frost-proof down to -25°C**

LMD: 29-03-24, 18:48

**PASTOR**  
DEUTSCHLAND



42781 Haan (NRW)  
Bahnhofstraße 48  
Deutschland

**MADE IN THE EU**  
**PASTOR-DEUTSCHLAND.DE**