

SK6P34

Cartridge operated foam fire extinguisher



TECHNICAL DATA

Type	SK6P34
Design	Cartridge operated foam fire extinguisher
Extinguishing agent quantity	6 l
Extinguishing agent	Foam
Propellant	CO ₂
Extinguishing performance	34A / 233B
Extinguishing agents units	34A (10) / 233B (15)
Functional range	0°C - +60°C
Operating time	44-46 s
Throwing distance	4-5 m
Hose / nozzle	Flexible, durable hose incl. extinguishing nozzle with optimised foaming
Weight	Approx. 10.85 kg
Height	Approx. 559 mm
Diameter	Approx. 150 mm

- Cartridge operated fire extinguisher, for more sustainability
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Maintenance-friendly premium appliance
- Glass fibre reinforced plastic fitting with push-button release
- M74-Threaded opening for best maintenance
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Internal corrosion-resistant propellant bottle
- Wall bracket and foot ring
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU
PASTOR-DEUTSCHLAND.DE