

SK9P43 GREEN

Cartridge operated foam fire extinguisher



PASTOR

Feuerlöscher

SCHAUM 9 L 43A 183B

-  **SICHERUNGSLASCHE
HERAUSZIEHEN**
REMOVE SAFETY DEVICE
-  **ROTE HAUBE
KRÄFTIG SCHLAGEN**
STRIKE ACTIVATION CAP
-  **LÖSCHPISTOLE
BETÄTIGEN**
SQUEEZE NOZZLE PISTOL



Vorsicht bei spannungsführenden Anlagen.
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Nach jeder Befüllung von Hochdruck-Elöscher-Systemen alle 2 Jahre mit Druckprüfgerät überprüfen.
Für alle Lösch-/Trenn- und Einstrahl-Verwendungen, die mit der Zulassung übereinstimmen.

TEMPERATURBEREICH: +5°C/+60°C ZULASSUNGSNUMMER:
LÖSCHMITTEL: 3,21 WASSER + 1,81 Pastorfoam TYP: SK9P43 GREER

NETTOGEWICHT: 900 g CO₂

PASTOR DEUTSCHLAND  42781 Haan (NRW) **MADE IN THE EU**
Baldenstraße 48 PASTOR-DEUTSCHLAND.DE
Deutschland

PASTOR

DEUTSCHLAND

SK9P43 GREEN

Cartridge operated foam fire extinguisher



TECHNICAL DATA

Type	SK9P43 GREEN
Design	Cartridge operated foam fire extinguisher
Extinguishing agent quantity	9 l
Extinguishing agent	Foam / Fluorine-free
Propellant	CO ₂
Extinguishing performance	43A / 183B
Extinguishing agents units	43A (12) / 183B (12)
Functional range	+5°C - +60°C
Operating time	55-60 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable hose incl. extinguishing nozzle with optimised foaming
Weight	Approx. 15.10 kg
Height	Approx. 614 mm
Diameter	Approx. 170 mm

- Cartridge operated fire extinguisher, for more sustainability
- Fluorine-free foam / Extinguishing agent contains no PFAS additives
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Maintenance-friendly premium appliance
- Glass fibre reinforced plastic fitting with push-button release
- M74-Threaded opening for best maintenance
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Internal corrosion-resistant propellant bottle
- Wall bracket and foot ring
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU
PASTOR-DEUTSCHLAND.DE