

# SK9P43

## Cartridge operated foam fire extinguisher



# PASTOR

### Feuerlöscher

SCHAUM 9 L 43A 233B

-  **SICHERUNGSLASCHE  
HERAUSZIEHEN**  
REMOVE SAFETY DEVICE
-  **ROTE HAUBE  
KRÄFTIG SCHLAGEN**  
STRIKE ACTIVATION CAP
-  **LÖSCHPISTOLE  
BETÄTIGEN**  
SQUEEZE NOZZLE PISTOL



Vorsicht bei spannungsführenden Anlagen.  
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Nach jeder Benutzung von handlichen Löschern gilt derselbe als 2 Jahre auf Feststellmisch überprüfbar.  
Für solche Löcher/Trichter und Ersatzteile verwenden, die mit der Zulassung übereinstimmen.

DRUCKTEMPERATUR: 0°C - 50°C ZULASSUNGSHOHE: SK9P43

LÖSCHMITTEL: T3/L WASSER - 10 L, Pastoralis TYP: SK9P43

TRICHTERWEITE: 70 mm

NETTOGEWICHT: 70 g

MADE IN THE EU

PASTOR DEUTSCHLAND



# PASTOR DEUTSCHLAND

# SK9P43

## Cartridge operated foam fire extinguisher



### TECHNICAL DATA

Type	SK9P43
Design	Cartridge operated foam fire extinguisher
Extinguishing agent quantity	9 l
Extinguishing agent	Foam
Propellant	CO <sub>2</sub>
Extinguishing performance	43A / 233B
Extinguishing agents units	43A (12) / 233B (15)
Functional range	0°C - +60°C
Operating time	58-60 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable hose incl. extinguishing nozzle with optimised foaming
Weight	Approx. 15.10 kg
Height	Approx. 614 mm
Diameter	Approx. 170 mm

- Cartridge operated fire extinguisher, for more sustainability
- High performance extinguishing agent for efficient fire-fighting, REACH-compliant
- Maintenance-friendly premium appliance
- Glass fibre reinforced plastic fitting with push-button release
- M74-Threaded opening for best maintenance
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Internal corrosion-resistant propellant bottle
- Wall bracket and foot ring
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

**PASTOR**  
DEUTSCHLAND



42781 Haan (NRW)  
Bahnhofstraße 48  
Deutschland

**MADE IN THE EU**  
**PASTOR-DEUTSCHLAND.DE**