WD9Z43

Stored pressure water fire extinguisher







PASTOR Deutschland

WD9Z43

Stored pressure water fire extinguisher



TECHNICAL DATA

Туре	WD9Z43
Design	Stored pressure water fire extinguisher
Extinguishing agent quantity	91
Extinguishing agent	Water
Propellant	N ₂
Extinguishing performance	43A
Extinguishing agents units	43A (12)
Functional range	+5°C - +60°C
Operating time	54-56 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable quality hose incl. extinguishing nozzle
Weight	Approx. 1 4.5 kg
Height	Approx. 640 mm
Diameter	Approx. 170 mm

- Stored pressure fire extinguisher, the budget device
- High performance extinguishing agent for efficient fire-fighting
- REACH-compliant
- Extinguishing agent contains no PFAS additives
- Durable M30 brass fitting with test and filling valve
- Intuitive handling with simple release mechanism
- When the locking pin is pulled the device is immediately ready for use
- Reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV weather-resistant hose with special nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Wall bracket
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant





42781 Haan (NRW) Bahnhofstraße 48 Deutschland

MADE IN THE EU PASTOR-DEUTSCHLAND.DE

Printing errors, mistakes, technical or other changes as well as changes in the availability of individual products are expressly reserved. PASTOR Deutschland GmbH, 2024